



#### LUMINAIRE REQUIREMENTS:

1. HOUSING – DIE-FORMED, COLD-ROLLED STEEL, WITH REINFORCEMENT RIBS FOR RIGIDITY; END CAPS SAME MATERIAL AS HOUSING, SECURED WITH TABS, SCREWS OR RIVETS. WHITE ENAMEL FINISH APPLIED AFTER FABRICATION. OPTIONAL LENGTHS OF 2 FT, 3 FT OR 4 FT.
2. LENS – ACRYLIC PRISMATIC (CLEAR PRISMATIC PATTERN A12) OR WHITE OPAL, WITH MINIMUM THICKNESS OF 0.125 IN.
3. LIGHT SOURCE – LINEAR T8, T5 OR T5HO FLUORESCENT TUBES WITH QUANTITY AND CHARACTERISTICS AS INDICATED IN LUMINAIRE SCHEDULE.
4. BALLAST – PROGRAMMED-START, CLASS P, THERMALLY-PROTECTED, HIGH POWER FACTOR (>0.9), ELECTRONIC TYPE WITH <20% THD AND 'A' SOUND RATING.
5. CERTIFICATION – UL 1598, DAMP LOCATION, UL 924 WHEN EQUIPPED WITH EMERGENCY BATTERY BACK-UP.
6. MOUNTING – SURFACE ON WALL.
7. OPTIONS – EMERGENCY BACK-UP, <10% THD BALLAST, DOWNLIGHT COMPONENT ONLY.
8. THIS SKETCH IS A NON-PROPRIETARY GRAPHIC REPRESENTATION OF A LUMINAIRE THAT MAY MEET THE SPECIFICATION REQUIREMENTS. IT IS NOT INTENDED TO INDICATE A CERTAIN MANUFACTURER OR PREFERENCE.

## WALL MOUNTED FLUORESCENT

REVISED:

APRIL 2016

LIGHTING PLATE:

NL-10