



LUMINAIRE REQUIREMENTS:

1. HOUSING – DIE-CAST ALUMINUM FRAME AND HEAT SINK WITH SILVER OR WHITE ENAMELED FINISH. APPROXIMATELY 1 FT x 4 FT.
2. LENS – IMPACT-RESISTANT ACRYLIC.
3. LIGHT SOURCE – SOLID STATE LEDS WITH MINIMUM 50K HOURS RATED LIFE AT L70, 3500K CCT UON, MINIMUM 80 CRI, MAXIMUM 4-STEP MCADAM ELLIPSE BINNING TOLERANCE FOR COLOR CONSISTENCY, AND MINIMUM EFFICACY OF 75 LUMENS/WATT. INITIAL LUMEN OUTPUT AS INDICATED IN LUMINAIRE SCHEDULE.
4. DRIVER – REMOTELY-LOCATED ABOUT CEILING, REPLACEABLE, HIGH-EFFICIENCY DRIVER WITH MINIMUM 0.9 PF, OPERATING VOLTAGE OF 120-277V, THERMAL MANAGEMENT, < 20% TOTAL HARMONIC DISTORTION. ON-OFF CONTROL, STEP-DIMMABLE OR FULLY DIMMABLE AS INDICATED.
5. CERTIFICATION – UL 1598, DLC QUALIFIED, AND ROHS COMPLIANT. COMPLIES WITH LM79, LM80 AND TM21 TESTING STANDARDS.
6. MOUNTING – SUSPENDED FROM HARD OR ACOUSTICAL TILE CEILING.
7. OPTIONS – 0-10V OR DALI SYSTEM DIMMING.
8. THIS SKETCH IS A NON-PROPRIETARY GRAPHIC REPRESENTATION OF A LUMINAIRE THAT MAY MEET THE SPECIFICATION REQUIREMENTS. IT IS NOT INTENDED TO INDICATE A CERTAIN MANUFACTURER OR PREFERENCE.

LED LINEAR PENDANT

REVISED:

APRIL 2016

LIGHTING PLATE:

NL-13