



NOTE: THIS SKETCH IS A NON-PROPRIETARY GRAPHIC REPRESENTATION OF A LUMINAIRE THAT MAY MEET THE SPECIFICATION REQUIREMENTS. IT IS NOT INTENDED TO INDICATE A CERTAIN MANUFACTURER OR PREFERENCE.

LUMINAIRE REQUIREMENTS:

1. HOUSING – EXTRUDED ALUMINUM WITH CLEAR ACRYLIC EDGE-LIT PANEL.
2. LIGHT SOURCE – SOLID STATE LEDS.
3. DRIVER – INTEGRAL, HIGH-EFFICIENCY DRIVER WITH MINIMUM 0.9 PF, OPERATING VOLTAGE OF 120-277V, THERMAL MANAGEMENT, AND < 20% THD.
4. CERTIFICATION – NFPA 101, UL LISTED FOR DAMP OR WET LOCATION, AND ROHS COMPLIANT.
5. MOUNTING – SURFACE MOUNTED ON CEILING AND/OR WALL.
6. OPTIONS – RED OR GREEN LETTERING, ONE- OR TWO-SIDED. BATTERY BACKUP.

EDGE-LIT EXIT SIGN

REVISED:

NOVEMBER 2020

LIGHTING PLATE:

NL-27