



NOTES:

1. ALL JOINTS SHALL BE FULL DEPTH SAWCUT.
2. ASPHALT SHALL BE COMPACTED PER SPECIFICATIONS.
3. ALL JOINTS SHALL BE SEALED ACCORDING TO SPECIFICATIONS.
4. ALL CATCH BASINS, VALVES, AND OTHER APPURTENANCES SHALL BE TACK COATED WITH AN ASPHALT EMULSION PRIOR TO THE APPLICATION OF ASPHALT CONCRETE.
5. THE TRENCH BACKFILL AND BASE COURSE MATERIAL SHALL BE COMPACTED PER SPECIFICATIONS.
6. CUTS SHALL NOT BE OPEN LONGER THAN 5 DAYS BEFORE COMPLETE BACKFILLING, COMPACTION AND PAVING OF THE CUT.
7. COMPACTED A.C. SHALL NOT EXTEND MORE THAN 1/4" ABOVE THE EXISTING SURFACE.
8. REPLACE PAVEMENT MARKINGS DISTURBED WITH PATCH.

| | |
|------------------------------|-----------------------|
| STANDARD DETAILS | |
| DRAWING TITLE. | |
| TYPICAL A. C. PAVEMENT PATCH | |
| DATE: | SCALE: |
| AUGUST 2020 | NONE |
| PLATE NO: | SPEC. SECT. <u>32</u> |
| R-10 | PAGE _____ |